



ESTIMATOR SHEET

Please be advised that these numbers will vary depending on many factors, such as existing surface texture and its porosity. Use these numbers as a general guideline.

These numbers account for a Bond Coat, Scratch Coat, and Texture Coat.

**** A bond and scratch coat are recommended on all applications! ****

Let the square footage of the job be your guide.

For example, if a job is **1300 sq. ft.**, simply add the columns of each product in the 300 and 1000 column.

So, for the Lace Texture, you will need approximately: **Additive** is 7 + 22 = 29 gallons.

Aggregate is 4 + 11 = 15 bags. **Top Coat** is 3 + 10 = 13 gallons.

LACE TEXTURE

Job Sq. Ft.	100	200	300	400	500	600	700	800	900	1000
Gallons of Acrylic Additive	3	5	7	9	11	14	16	18	20	22
# of 50 lb. bags of Aggregate	2	3	4	5	6	7	8	9	10	11
Gallons of Top Coat Color Sealer (2 coats)	2	4	6	8	10	12	14	16	18	20

FLAGSTONE & SALTILLO TEXTURES - (Not stamped)

Job Sq. Ft.	100	200	300	400	500	600	700	800	900	1000
Gallons of Acrylic Additive	3	6	9	12	15	18	21	24	27	30
# of 50 lb. bags of Aggregate	2	3	5	6	8	9	11	12	14	15
Top Coat (use as a stain)	(Use 10 parts of clear sealer or water to 1 part of Top Coat Color)									
Gallons Clear Sealer	½	1	1 ½	2	2 ½	3	3 ½	4	4 ½	5



STAMP OVERLAY

Use regular Aggregate for the Scratch Coat. Use Stamp Overlay Aggregate for the texture coat.

Job Sq. Ft.	100	200	300	400	500	600	700	800	900	1000
Gallons of Acrylic Additive	9	15	21	27	33	40	48	55	60	70
# of 50 lb. bags of Aggregate (regular aggregate – for Scratch Coat only)	½	1	1 ½	2	2 ½	3	3 ½	4	4 ½	5
# of 50 lb. bags of Overlay Aggregate (Texture Coat)	4	8	12	16	20	24	28	32	36	40
Gallons of Bubble Gum Release	½	1	1 ½	2	2 ½	3	3 ½	4	4 ½	5
Use the coloring method or your choice – Powder Colorants, Decorative Stain, or diluted Top Coat.										
Gallons Southwest Seal or High Gloss Sealer	½	1	1 ½	2	2 ½	3	3 ½	4	4 ½	5

If you have any application questions, please do not hesitate to call us at **888.440.3320** or email us at info@prefdeck.com. Visit our website at www.prefdeck.com.

Do not apply any Preferred Deck products when the deck temperature is less than 50 degrees.
We suggest using an infrared temperature gun, which can be purchased at Napa Auto Parts.

Preferred Deck Systems
 7534 W. Madison St.
 Tolleson, AZ 85353
888.440.3320
www.prefdeck.com